

HMR35 Series Micro Precision Regulator



HMR35

- 1. The valve body is made of engineering plastic, the product is light weight and compact, making it ideal for use on portable systems, such as ventilators, dental equipment, etc.
- 2. Special overflow structure consisting of spring, seal and valve core, sensitive movement, high regulating accuracy and good flow characteristics. Flange installation, simple and convenient.

Specification

Model	HMR35
Rated Flow	260L/min
Highest Working Pressure	1.0Mpa
Working Medium	Compressed air
Ambient and Fluid Temperature	0~60℃
Pressure Regulating Range	0.05~0.35Mpa
Installation	Bottom flange installation
Installation position	Any where

XS Series Air Source Treatment Unit




XSFC-200

Ordering Code

XS	FC	200
Series XS series	Function code FC: Filter&Regulator+Lubricator FR: Regulator&Filter L: Lubricator	Port Size 200: G1/4" 300: G3/8" 400: G1/2"

Graphic Symbol



Specification

Model	XSFC/FR/L-200	XSFC/FR/L-300	XSFC/FR/L-400
Port Size	G1/4"	G3/8"	G1/2"
Pressure Gauge Bore	G1/8"	G1/8"	G1/8"
Ensured Pressure Resistance	1.5MPa		
Highest Working Pressure	1.0MPa		
Environment and Fluid Temperature	5~60℃		
Protective Cover	Available		

The product has the function of filter, regulator and lubricator. Its structure is tight, flow rate is large, output is steady and installation is simple. The element has a pressure gauge, installation bracket and lubricator. The lubricator can non-stop gas. All have a cup-shaped protective cover. Use safely and appearance is elegant.

XN Series Air Source Treatment Unit



XNFC07-200



XNFR07-200



XNF07-200



XNL07-200



XNR07-200

Specification

Model	XNFC07-200	XNFR07-200	XNF07-200	XNL07-200	XNR07-200
Operating Fluid	Compressed Air				
Range of Adjustable Pressure	0-0.8Mpa				
Operating Temperature Range	-20~50℃				
Joint pipe bore	G1/4"				

XU Series Air Source Treatment Unit



XUC-04

XUWL-04

XUW-04

Ordering Code

XU	C	02	□
Series XU Series	Function code C: Filter+Regulator+Lubricator WL: Filter&Regulator+Lubricator W: Filter&Regulator R: Regulator F: Filter L: Lubricator	Port Size 02: G1/4" 03: G3/8" 04: G1/2" 06: G3/4" 08: G1"	Drain Type Blank: Manual D: Auto Drain Type

Specification

Model	XUC/WL/W-02 XUF/R/L-02	XUC/WL/W-03 XUF/R/L-03	XUC/WL/W-04 XUF/R/L-04	XUC/WL/W-06 XUF/R/L-06	XUC/WL/W-08 XUF/R/L-08
Port Size	G1/4"	G3/8"	G1/2"	G3/4"	G1"
Gauge	1/4"				
Operating Fluid	Air				
Pressure Range	0.05~0.85MPa				
Max. Flow rate (NI/min)	2050		2500	7900	8100
Ambient Temperature	-10~60℃				
Filter Precision	Standard: 20µm				
Oil Recommended	Turbine oil (ISO VG32)				
Cup Material	Polycarbonate				
Structure	Diston type				