










Solenoid Valve Accessories

Model	Product	Specification	Model	Product	Specification
PU220 Series Diaphragm		PU220-03A PU220-04A PU220-06A PU220-08A	PU225 Series Diaphragm		PU225-03A PU225-04A PU225-06A PU225-08A
2W Series Diaphragm		2W-160-15 2W-200-20 2W-250-25 2W-350-35 2W-400-40 2W-500-50	2L(US) Series Piston		2L-170-10/15/20 2L-200-25 2L-350-35/40 2L-500-50

Explosion-proof Coil & Timer

Model	Product	Specification	Model	Specification
Product No. XC280 Product Type 0980,0981				Normal Voltage AC220V,AC110V,AV24V,DC24V,DV12 Other Voltage can be customized Normal Power AC5.5VA,DC5W Other Power can be customized Explosion-proof level Exm I / II T4 Connection Type Connector Type Applicability EX-proof Solenoid Valve
Product No. XC281 Product Type 1380,1381		 Supply voltage		Normal Voltage AC220V,AC110V,AV24V,DC24V,DV12V Other Voltage can be customized Normal Power AC5.5VA,DC5W Other Power can be customized Explosion-proof level Exm I / II T4 Connection Type Connector Type Cable Applicability EX-proof Solenoid Valve
Valve Timer-1				Supply voltage 24..240V AC/DC-50Hz/60Hz for "CE" marked Absorption current Timer Operating current 4 mA max temperature -10°C +50°C Class protection IP65-EN60529 Switch holding voltage 400V Max Switch capacity 1A Inrush current 10A for 10ms Duty cycle 100% ED Switch Life 3×10 ⁸ Time ON From 0.5 to 10s. Time OFF From 0.5 to 45s. Indicators Yellow LED Manual override Test Termination DIN43650A

Pneumatic Accessories

Users usually overlook these accessories, but they are most necessary element in pneumatic system. XCPC knows the importance of these small parts, we never give up the high quality standard. The pneumatic accessories we can offer is plastic fittings, brass fittings, quick connectors, pipe fittings, quick couplers, air pipe(PU/PE/PA) and air guns etc.

